

FEATURES:

• No Convert Adapter Required

- Standard 3.5 inch design fit in all pc case
- USB 2.0 specification interface
- USB 2.0 backward compatible with USB1.1
- Compliant with USB Mass storage device class specification

SPECIFICATIONS:

Memory Slots	
Memory Slots MS Slot	MS MS DUO MS Dro MS Dro Duo MS MagicCato MS Dro MagicCato
1013 3101	MS, MS-DUO, MS Pro, MS Pro-Duo, MS MagicGate, MS Pro MagicGate,
	MS-DUO MagicGate, MS Pro-DUO MagicGate etc.
CF Slot	CF I/II, CF Ultra II, CF Extreme III, Micro Drive, Magicstor
SD Slot	SD, miniSD, MMC-I, MMC-II, MMC4.0, MMC Dual Voltage, RS-MMC, RS-MMC
	Dual Voltage, RS-MMC 4.0, T-Flash/Micro SD(Convert Adapter Required)
SMC Slot	SM, SM ROM, eXcellent Digital, xD
Indicators	Power & Data accessing indicator
Bus Interface	USB2.0 or 1.1 (5-pin Housing USB Cable)
Power Supply	5V by USB Port
Operation Current	< 200mA
Suspend Current	< 500mA
Operating Temperature	0 ~ 70°C
Stock Temperature	-20 ~ 60°C
Cable	Pin Housing Type 50cm lengths
Dimensions	120 * 102 * 25.5 mm (D*W*H)
Certification	FCC Class B, CE
System OS Support	- Windows 98/SE, Windows ME, Windows 2000, Windows 2003 Server,
	Windows XP
	- Mac OS 9.2 or Higher
	- Linux OS 2.4.X or Higher
NOTE: Specifications are subject to change without notice. Brands and names are the properties of their	

NOTE: Specifications are subject to change without notice. Brands and names are the properties of their respective owners.